# RT112 10.1 Inch Android Rugged Tablet

5G & Wi-Fi 6E | Longevity QCM5430 Processor | IP67 & 1.5M Drop

## Powered by Android 13 OS with GMS & AER Certified

The RT112 is a 10.1-inch Android 13 rugged tablet equipped with an advanced 64-bit Hexa Cores CPU capable of reaching speeds up to 2.1 GHz. It effortlessly handles demanding tasks while ensuring smooth multitasking. With the distinction of Google Certification, encompassing Google Mobile Service (GMS) and Android Enterprise Recommended (AER) endorsement, the dual certification assures a secure and efficient business environment.

#### Premier Barcode Reading Performance

Featuring powerful 1D/2D scanning capabilities and utilizing premier 2D barcode scanning technology, the RT112 rugged tablet offers an optional engine that enables barcode reading at distances of up to 10m with 5G and Wi-Fi 6E connectivity. This provides the perfect solution for the warehousing, retail and logistics environments, allowing users to enjoy high-performance barcode reading, whether it's from a short or long distance, and optimize their work efficiency.

### Seamless and Connectivity via Wireless Communication

Featuring Bluetooth® 5.2, wireless Wi-Fi 6E with fast roaming and 5G connectivity for real-time data collection, user can scan the item and instantly connect to the backend system to find out the quantity in stock or make an online order for customers. The RT112 delivers a seamlessly work experience and improves productivity for various applications, making it faster downloads and uploads at user's fingertips on the most reliable networks for your business.

#### 5G IOT Platform

Equipped with the Qualcomm 5430 5G IoT Platform, the RT112 offers seamless integration into the future of technology. Its robust 5G capabilities ensure lightning-fast data transfer and a responsive online experience, all while being optimized for the demands of the Internet of Things. With a focus on longevity, the RT112 boasts an extended life cycle, making it an ideal investment for those seeking a device that will remain relevant and efficient for years to come.

#### **Durable Design**

The RT112 enhances the industrial durable protection with features including IP67 dustproof, waterproof, and 1.5 meters resistance to fall protection. That means it covers fully protected from dust and can survive in 1 meter of water for up to 30 mins. The MIL-STD-810H standard assures an overall environmental vibration and humidity. The light tablet with a slim 12mm edge is designed for workers to comfortably capture data and check inventory in high portability from day to night. For an easy touch and view, the 10.1 "display supports glove and wet touch mode with 500 nits.

#### Features

- Android 13 with GMS & AER Certified
- 10.1" (1920 x 1200) LCD display with Gorilla® Glass (500 nits)
- Lightweight but durable: 690g with 12mm
- Rugged Design: IP67 rated, 1.5M drop and MIL-STD-810H certified
- Wireless Communication: 5G & Wi-Fi 6E
- 5G IOT Platform (Qualcomm 5430): Support Long Life Cycle





# RT112 Specifications

System Features			- Symbologies		
OS			1D	Codobor Cod	a 11 Cada 120 Cada 2 af E. Cada 20 Cada 02
GMS certified	Android 13.0 with AER certified GMS certified		ID.		e 11, Code 128, Code 2 of 5, Code 39, Code 93 JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved
CPU	Qualcomm Snapdragon™ 5430 Processor, 64bits,				2 of 5, MSI, GS1 Databar, UPC-A, UPC E,
CFU					3 with Extended Coupon Code, Coupon GS1 Code
Manaan	Hexa Cores up to 2.1 GHz (Option: Octa Cores) 6GB RAM + 128GB Flash				
Memory	(Option: 8GB RAM + 128GB Flash)		2D		AN-UCC Emulation, GS1 Data Bar Codablock F, PDF417, MicroPDF417, Aztec Code,
AI			20		MaxiCode, QR Code, Chinese Sensible (Han Xin),
	6th Gen Qualcomm Al Engine Qualcomm® Trusted Execution Environment (TEE)				
Others			Destel	Grid Matrix, D	
			Postal		st, British Post, Canadian Post, China Post,
Display					t, Korea Post, Netherlands Post, Planet Code,
10.1" (1920 x 1200) LCD Display 500 nits				Postnet	
Gorilla® Glass, M	ulti-Touch User Interface with Capacitive, stylus,		Communication		
glove (thickness	≤4 mm), wet-finger Compatibility		Camera	Rear:13M (wit	th auto-focus and LED flash, Support Google Arcore
			Carriera	& Depth API)	
Buttons / Key	pad Indicator			Front:5M (wit	h fixed focus)
6 Physical Button			Bluetooth®	Bluetooth <sup>®</sup> 5.	
Power, Volume+/			WLAN		GHz & 5GHz & 6GHz
Programable Key	x 1				Band Simultaneous (DBS)
					/b/g/n/ac/ax/d/e/h/i/k/r/v (2x2 MU-MIMO)
RFID			WWAN (Optional)	Support 2G/30	
				5G FR1 Sub 6	
Support HF/NFC	A Trans D) (CO15000 Million E-line/(CO/(EC10000)				/N28/N41/N48/N66/N71/N77/N78/N79 (4x4 MIMO)
15014443-4 (Type	e A, Type B), ISO15693, Mifare, Felica(ISO/IEC18092)				- Bands 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 28, 66, 71
					Bands 38, 39, 40, 41, 48
I/O Interfaces					PA+ – Bands 1, 2, 5, 8
USB	USB3.1 Type-C x 1				S/EDGE (850/900/1800/1900 MHz)
POGO PIN	POGO pin				a, SMS and Voice capabilities
SIM Slot	Nano SIM x1 and Micro SD Card x 1			*n48 & B48 fo	
31111 3101	(or Nano SIM x 2)		GPS		Glonass, Galileo, QZSS, NavIC and SBAS
Audio	Dual-speakers			(for WWAN m	
Addio	MIC*2		Sensors		ccelerometer (G-sensor), E-compass, Light &
	(noise cancelling & Background noise depression)			Proximity Sen	
	(noise surrouning a basinground noise asprossion)				
			Enclosure		
Power Source	9		Dimensions	260x16	65x12mm
Main Battery	8800mAh (removable)		Weight	690g	
			Environment		
				0.000	EEOC
Software			Operating temperatur		
	ftware Solutions and utilities such as Airwatch, SOTI,		Storage temperature	-40°C ~	- 70 C
Ivanti Wavelink, a	ηα Ινιοφομιηκ		Drop test to Concrete		
			Environmental Sealing	•	DE9/ (Non Condension)
Regulatory Ap	pprovals		Relative Humidity Vibration and Shock to		95% (Non-Condensing) [D-810H. Method 516.8. Procedure IV
CE, UKCA, FCC,	C, NCC, BSMI, VCCI, TELEC, CCC, SRRC, BQB, RoHS,			est IVIIL-ST	
REACH		_	What comes in t	ho how	- Accessories
			RT112 Battery Pack		Rotatable Hand Strap Shoulder Strap
			USB-C Adaptor		Screen Protector
SGS UKAS	Green Product				Office Cradle
Headquarters					Vehicle Cradle
Taipei, Taiwan					Capacitive Stylus Pen (5.5mm) w/ Coil Strap
	com e-mail: info@hq.ute.com				
unitech Amer	ica		unitech Europe Tilburg / Netherlands	\$	
Los Angeles			http://eu.ute.com		ute.com
	n e-mail: info@us.ute.com n info@can.ute.com		unitech Japan		
Mexico			Tokyo		
	m e-mail: info@latin.ute.com		http://jp.ute.com e	⊢mail: info@jp.u	ute.com

unitech Asia Pacific & Middle East Taipei http://apac.ute.com info@apac.ute.com / info@india.ute.com http://mideast.ute.com info@mideast.ute.com

unitech Greater China Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com



Specifications subject to change without notice. Copyright 2024 unitech Electronics Co., Ltd. All rights reserved. unitech is a registered trademark of unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.



UNote

A simple text viewer and editor for use in your work flows.



Auto-run apps when device boots up.



For versatile functions of RFID command via integrating with Unitech RFID Readers.



An easy and fast way to get logs from a device.



Enterprise Keyboard gives various methods for user to input data to enhance efficiency and productivity.